

Item	Model	Unit	T15BML	T15BMS	T9.9BML	T9.9BMS
Overall length		mm(in.)	870 (34.4)			
Overall width		mm(in.)	328 (12.9)			
Overall height		mm(in.)	1166 (45.9)	1039 (40.9)	1166 (45.9)	1039 (40.9)
Transom height		mm(in.)	567 (22.3)	440 (17.3)	567 (22.3)	440 (17.3)
Weight		kg	37.5	36	37.5	36
Full throttle operating range		r/min	4500-5500			
Maximum output		kw(HP)@r/min	11(15)@5000		7.3(9.9)@5000	
Idling speed (Neutral)		r/min	700-800			
Engine type			2-Stroke			
Cylinders			L2			
Displacement		cm ³	246			
Bore x stroke		mm(in.)	56x50(2.20x1.97)			
Ignition system			CDI			
Control system			Tiller control			
Starting system			Manual start			
Gear positions			Forward-Neutral-Reverse			
Gear ratio			2.08(27/13)			
Trim and tilt system			Manual tilt			
Fuel tank capacity		L	24			
Maximum fuel waste		L/h	7.9		5.1	
Engine oil capacity (Without oil filter)		L	(Fuel oil ratio:50:1)			
Gear oil capacity		cm ³	250			
Propeller options*		in	3-9 1/4 X8*			

*Propeller choice will vary by boat size and application.